

Lamp Included!




**PR Series
6" Extended Pole Mount**

Parking/Roadway


You'll see an increase in street side efficiency with the redesigned reflector and repositioned lamp in the PR Series. The 12-inch and 16-inch housings of the Parking/Roadway Light have a Type III asymmetric distribution pattern. The 22-inch housing has Type II asymmetric distribution. Ideally suited for roadway applications, parking areas or for building-mounted security lighting.

Three Sizes:

- 12" square x 5" deep (305 x 127 mm)
- 16" square x 6.5" deep (406 x 165 mm)
- 22" square x 9.3" deep (559 x 235 mm)



Typical Candlepower Distribution of 400W MH Parking/Roadway Light. (Front View)



Isofootcandle plot of one 400W MH Parking/Roadway Light at 30' (9.1 m) mounting height, and 0° tilt above horizontal.

Order Information

Housing Size (sq.)	Wattage/Lamp	Catalog Number	Mounting Code (Insert Code at * in Catalog #)
12"	150W PSMH	MPR*615-M	1 = 1-1/2" Close Pole Mount
16"	150W PSMH	PR*615-M	2 = 6" Extended Pole Mount
16"	250W PSMH	PR*625-M	3 = 2" Adjustable Fitter
16"	320W PSMH	PR*632-M	4 = Yoke Mount
16"	400W PSMH	PR*640-M	6 = 1/2" Adjustable Fitter (12" housing only)
22"	750W PSMH	PR*675-M	8 = Without Mounting (hardware) (factory-drilled)
12"	50W MH	MPR*405-M	K = Round Tube Off-Center Tenon Mount (16" housing only) (For 2-3/8" or 3" O.D.)
12"	70W MH	MPR*407-M	M = Round Tube Off-Center Direct Mount (16" housing only)
12"	100W MH	MPR*410-M	W = Wall Mount
12"	175W MH	MPR*417-M	
16"	175W MH	PR*417-M	
16"	250W MH	PR*425-M	
16"	400W MH	PR*440-M	
22"	1000W MH	PR*499-M	
12"	35W HPS	MPR*503-1	
12"	50W HPS	MPR*505-D	NOTE: When using multiple 22" sq. housings at 90° configuration, a special 12" arm is required; see page 148.
12"	70W HPS	MPR*507-M	
12"	100W HPS	MPR*510-M	
12"	150W HPS	MPR*515-M	
16"	250W HPS	PR*525-M	
16"	400W HPS	PR*540-M	
22"	1000W HPS	PR*599-M	

◀ Some states prohibit these products from being sold.

* Specify Mounting (additional cost)

Other lamp wattages available—consult factory

◉ Reduced envelope lamp. ED28 for 320 & 400W PSMH and 400W MH.

Options: (Factory-installed)	Change Suffix To	Add After Suffix
120V Reactor ballast (50–150W HPS 12" housing only)	1	
277V Reactor Ballast (PSMH only)	27	
347V ballast (50W HPS only)	6	
480V ballast (PSMH, 175–1000W MH & 70–1000W HPS only)	5	
480V ballast (70–100W MH only)	5	
Tri-volt ballast (PSMH, MH & 70–1000W HPS only)	T	
Single Fuse (277V Reactor, 120V, 277V or 347V)	27, 1, 2 or 6	F
Dual Fuse (208V, 240V or 480V) (n/a Canada)	3, 4 or 5	F
Quartz Standby (delay-relay type) (includes 100W Q lamp) (n/a 277V Reactor)	Q	
Uplight Lens Frame (Backlight Shield included)	U	
Button Photocell (Factory-installed with all mountings other than 2" Adjustable Fitter)		
NOTE: n/a on 1000W w/120V; all 480V	27, 1, 2, 3, 4 or 6	P
External Photocell (Factory-installed) (Page 131)		
For fixtures w/1000W, 120V	1	P
For fixtures w/480V	5	P

Accessories:

(Field-installed)	12"	16"	22"
Wire Guard	FWG-12	FWG-16	FWG-22
Backlight Shield	SBL-12	SBL-16	SBL-22

Button Photocell (Field-installed in fixtures with 2" Adjustable Fitter)	Catalog #
For fixtures w/120V (n/a on 1000W)	PC-1
For fixtures w/208, 240 or 277V	PC-2
For fixtures w/347V	PC*6

Mountings	Page 114
Catalog Number Logic/Voltage Suffix Key	Page 113
Optical Systems	Pages 102–105
Accessories	Page 131
Mounting Alternatives	Pages 148–149
Mounting Brackets	Pages 150–151
Poles	Pages 152–159

Dependability... **DIRECT!**

(800) 236-7000, 7 a.m. to 6 p.m. CT

Fax: (800) 236-7500 • www.ruudlighting.com